

tre Diesel

19.50.01

ing filter/  
uel system,  
istributor

mentor dis-  
with a sedi-  
ained only  
, priming is  
iced by fuel  
the tank.  
as been dis-  
ie body, or  
t has been  
eaned, then  
allows:  
the engine  
ough in this  
riming pro-  
njo bolt on  
ier.  
lever on the  
el free from  
pump lever  
rating cam  
, otherwise  
iming lever  
jo bolt with



without special equipment  
in a bath of paraffin  
rocker arm several times

ump clean of the bath and  
operate the rocker arm  
mp is empty, then place a  
the inlet port and operate  
several times. A distinct  
id be heard when the  
oved from the inlet port,  
at a reasonable degree of  
been developed.

25 To remove the  
the pump  
by return the  
rocker arm  
diaphragm  
maintained  
with the  
Push the  
to lock  
the cover  
the cover  
26 secure by  
Trace top  
aligning  
assembly  
not tight  
priming  
and any  
body with the diaphragm  
diaphragm assembly, hold  
the pump  
NOTES: The 2  
be approxi  
over the spring with the  
of the pump  
appreciable  
beyond the  
improper  
release of the  
in accordance  
29 2% fine  
and meet  
this clip  
centrally  
NOTES: Do not  
prevent cracking  
The pump  
30 immerse  
and open  
diaphragm outer edges should  
to mesh.  
31 Hold the  
the faces when fitted, any  
continue  
division of the diaphragm  
and the  
finger out  
rocker at  
stroke.   
finger is  
demolish  
station

26 To remove the  
the pump  
by return the  
rocker arm  
diaphragm  
maintained  
with the  
Push the  
to lock  
the cover  
the cover  
27 secure by  
Trace top  
aligning  
assembly  
not tight  
priming  
and any  
body with the diaphragm  
diaphragm assembly, hold  
the pump  
NOTES: The 2  
be approxi  
over the spring with the  
of the pump  
appreciable  
beyond the  
improper  
release of the  
in accordance  
29 2% fine  
and meet  
this clip  
centrally  
NOTES: Do not  
prevent cracking  
The pump  
30 immerse  
and open  
diaphragm outer edges should  
to mesh.  
31 Hold the  
the faces when fitted, any  
continue  
division of the diaphragm  
and the  
finger out  
rocker at  
stroke.   
finger is  
demolish  
station

25 To remove the  
the pump  
by return the  
rocker arm  
diaphragm  
maintained  
with the  
Push the  
to lock  
the cover  
the cover  
26 secure by  
Trace top  
aligning  
assembly  
not tight  
priming  
and any  
body with the diaphragm  
diaphragm assembly, hold  
the pump  
NOTES: The 2  
be approxi  
over the spring with the  
of the pump  
appreciable  
beyond the  
improper  
release of the  
in accordance  
29 2% fine  
and meet  
this clip  
centrally  
NOTES: Do not  
prevent cracking  
The pump  
30 immerse  
and open  
diaphragm outer edges should  
to mesh.  
31 Hold the  
the faces when fitted, any  
continue  
division of the diaphragm  
and the  
finger out  
rocker at  
stroke.   
finger is  
demolish  
station

25 To remove the  
the pump  
by return the  
rocker arm  
diaphragm  
maintained  
with the  
Push the  
to lock  
the cover  
the cover  
26 secure by  
Trace top  
aligning  
assembly  
not tight  
priming  
and any  
body with the diaphragm  
diaphragm assembly, hold  
the pump  
NOTES: The 2  
be approxi  
over the spring with the  
of the pump  
appreciable  
beyond the  
improper  
release of the  
in accordance  
29 2% fine  
and meet  
this clip  
centrally  
NOTES: Do not  
prevent cracking  
The pump  
30 immerse  
and open  
diaphragm outer edges should  
to mesh.  
31 Hold the  
the faces when fitted, any  
continue  
division of the diaphragm  
and the  
finger out  
rocker at  
stroke.   
finger is  
demolish  
station

25 To remove the  
the pump  
by return the  
rocker arm  
diaphragm  
maintained  
with the  
Push the  
to lock  
the cover  
the cover  
26 secure by  
Trace top  
aligning  
assembly  
not tight  
priming  
and any  
body with the diaphragm  
diaphragm assembly, hold  
the pump  
NOTES: The 2  
be approxi  
over the spring with the  
of the pump  
appreciable  
beyond the  
improper  
release of the  
in accordance  
29 2% fine  
and meet  
this clip  
centrally  
NOTES: Do not  
prevent cracking  
The pump  
30 immerse  
and open  
diaphragm outer edges should  
to mesh.  
31 Hold the  
the faces when fitted, any  
continue  
division of the diaphragm  
and the  
finger out  
rocker at  
stroke.   
finger is  
demolish  
station

25 To remove the  
the pump  
by return the  
rocker arm  
diaphragm  
maintained  
with the  
Push the  
to lock  
the cover  
the cover  
26 secure by  
Trace top  
aligning  
assembly  
not tight  
priming  
and any  
body with the diaphragm  
diaphragm assembly, hold  
the pump  
NOTES: The 2  
be approxi  
over the spring with the  
of the pump  
appreciable  
beyond the  
improper  
release of the  
in accordance  
29 2% fine  
and meet  
this clip  
centrally  
NOTES: Do not  
prevent cracking  
The pump  
30 immerse  
and open  
diaphragm outer edges should  
to mesh.  
31 Hold the  
the faces when fitted, any  
continue  
division of the diaphragm  
and the  
finger out  
rocker at  
stroke.   
finger is  
demolish  
station

25 To remove the  
the pump  
by return the  
rocker arm  
diaphragm  
maintained  
with the  
Push the  
to lock  
the cover  
the cover  
26 secure by  
Trace top  
aligning  
assembly  
not tight  
priming  
and any  
body with the diaphragm  
diaphragm assembly, hold  
the pump  
NOTES: The 2  
be approxi  
over the spring with the  
of the pump  
appreciable  
beyond the  
improper  
release of the  
in accordance  
29 2% fine  
and meet  
this clip  
centrally  
NOTES: Do not  
prevent cracking  
The pump  
30 immerse  
and open  
diaphragm outer edges should  
to mesh.  
31 Hold the  
the faces when fitted, any  
continue  
division of the diaphragm  
and the  
finger out  
rocker at  
stroke.   
finger is  
demolish  
station

14 It is unlikely that the  
crank will ever  
out may be removed  
tag on each side  
and spring the  
threw the cork  
le.

15 Clean and  
filter disc must be  
Examined and  
fit tightly around  
per casing. (2%)  
Replace  
align assembly if any  
cracking or porosity  
is present.

16 Examine  
as necessary  
Sediment  
of damage  
neck  
meals)  
17 Renew  
of hard  
present  
rated at  
pivo. 2  
phragm  
Spring  
correct  
22 Test  
suction.  
23 Check  
for dis

18 Sediment  
of damage  
neck  
meals)  
17 Renew  
of hard  
present  
rated at  
pivo. 2  
phragm  
Spring  
correct  
22 Test  
suction.  
23 Check  
for dis

19 Renew  
of hard  
present  
rated at  
pivo. 2  
phragm  
Spring  
correct  
22 Test  
suction.  
23 Check  
for dis

20 Only valve  
can be replaced,  
if used,  
for air tightness  
and lower casing  
using a straight edge  
3. It is safe to seek  
owners and the  
ages

21 Spring  
correct  
22 Test  
suction.  
23 Check  
for dis

24 Reassemble  
rocker  
retainer



