





ROTARY PUMPS CAV/DPS

Pics	STAR Ref/	Orig.Reference	Descriptions
1	36107	7167-60	plug prot/yellow
2	31493/25		on request
3	31613		on request
4	36280	139-131 139-184	plastic cap protection DPA 9x36
5	36496	1903240000	lead seal 05606-62
6	36499	7135-105	seal wire mm.200
7	52257	5339-966	washer copper 12.8x16x1.5
8	31610		on request
9	36496	1903240000	lead seal 05606-62
10	36499	7135-105	seal wire mm.200
11	31906	7174-127a=22159	oil seal high
11	31934	7174-856	oil seal short
12	31605		on request
13	31606		on request
14	31607		on request
15	31608		on request
16	31609		on request
17	36132/01	7139-2C	manual lock TRAX FIAT
18	31060	1410210012	DPA o-ring shaft
19	36276	7174-828es	throttle shaft dps pump
20	36502	7167-74EA	d/valve DPS FORD TRANSIT
21	36632		on request
22	36102		washer 6x12x1
23	31634		on request
24	31614		on request
24	31633		on request
26	31617		on request
27	31618		on request
28	52522/01	7174-274= 7182-491	DPS gasket cover
28	52522/02	7174-491	gasket
29	31616		on request
30	31615		on request
31	36387	7182-580A	diaphragm DPS

Pics	STAR Ref/	Orig.Reference	Descriptions
32	36510		clamp DPS
33	36506		clamp DPS
34	36504	9103-203	clamp
35	36528	7180-19R=7180-668R	head rotor
36	31639		on request
37	36650	7135-24B	modification ball DPS
38	31604		on request
39	31930	7177-38A	oil seal DPS
40	31061	5855-30BD	seal ring DPA
41	36303	NW5-18W4	washer DPA 8x13x1,5
42	36130	5330-362	nut cap
43	36132/02	7123-261=7123-261B=7123-261N	stud PERKINS FORD
44	31063	5855-30FR	o-ring (ex 7139-821)
45	52523/01	7182-198	gasket a/advance DPS
46	36622		on request
47	31628		on request
48	31627		on request
49	31066	5855-30BC	o-ring DPA head mm.2
50	31014/01		on request
51	31602	5339-808=5339-964	washer copper 6x3.6x0.8
52	36100	5936-332C	washer steel DPA mm.2,0
53	36104	9007-391=9007-391A	washer for valve
54	36165/01	7174-842E	screw
55	36139/01		connection
56	36641		on request
57	31640		on request
58	36619		on request
59	31620		on request
60	31638		on request
61	36132/01	7139-2C	manual lock TRAX FIAT
62	36621		on request
63	36623		on request
64	36625		on request

[illegible]